

ZX350e

Ultracompact high brightness laser projector



- **Bright XGA DuraCore laser projector - 3700 lumens**
- **Small form factor for easy installation - 1.1x zoom, 360-degree and portrait projection**
- **DuraCore laser technology - 30,000 hours maintenance-free laser light source**
- **Built with the environment in mind - Long laser life span, incorporating Post consumer recycled material**



The ZX350e is Optoma's most compact hassle free XGA DuraCore laser projector to date. Designed for maintenance-free continuous operation, it can be installed in virtually any orientation and location due to the small and lightweight footprint.

Designed with the environment in mind the ZX350e cuts power by 47% vs a typical Optoma lamp based product. Optoma have looked to minimize product design to cut logistic impacts on the environment cutting CO2 and reducing our overall carbon footprint.

Specifications

| | |
|--------------------------------|--|
| Display and image | |
| ProjDisplayTechnology | DLP™ |
| ProjNativeResolution | XGA (1024x768) |
| ProjBrightnessBrightLumens | 3.700 |
| ProjContrastRatio | 300.000 |
| ProjContrastRatioDynamic | 2.000.000 |
| NativeAspectRatio | 4:3 |
| SupportedAspectRatio | 4:3, 16:9 |
| ProjKeystoneCorrectionVertical | +/-40° |
| ProjDisplayableColoursMillions | 1073.4 |
| ProjHorizontalScanRateKhz | 15 ~ 140 |
| ProjVerticalScanRateHz | 24 ~ 120 |
| ProjUniformityPercent | 75 |
| Screen size | 0.76m ~ 7.62m (30" ~ 300") diagonal |
| Lamp info | |
| ProjLightSource | Laser |
| ProjLaserHours | 30.000 |
| Optical | |
| ThrowRatio | 1.94:1 ~ 2.16:1 |
| ProjectionDistanceMetres | 1m ~ 10m |
| FixedLensZoom | 1.1 |
| FixedLensZoomType | Manual |
| FixedLensFocalLength | 21.85 ~ 24.01 |
| ProjNativeOffset | 115% |
| Connectivity | |
| Connections | Inputs 2 x HDMI 1.4a 3D support Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232 |
| General | |
| NoiseLevelTypicalDb | 27 |
| PcCompatibility | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| Proj2DCompatibility | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) |
| Proj3DCompatibility | Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 |
| Proj3DType | Full 3D |
| ProductSecurity | Security bar, Kensington Lock, Password protected interface |
| IP rating | IP6X |
| OSDLangs | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| TwentyFourSevenOperation | Yes |
| ThreeSixtyDegreeOperation | Yes |
| OperatingConditions | 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m |
| SpeakerCount | 1 |
| SpeakerWatts | 15 |
| In the box | Power adaptor Remote control Basic user manual |
| Power | |
| PowerSupply | 100V ~ 240V, 50-60Hz |
| PowerConsumptionWattsStandby | <0.5 |
| PowerConsumptionWattsMin | 89 |
| PowerConsumptionWattsMax | 140 |
| Weight and dimensions | |
| ProductDimensions | 274 x 216 x 114 |
| Gross weight | 4.2 kg |
| Net weight | 3 kg |

